Philips
Component video cable

6 ft

SWV6302D

Enjoy the ultimate viewing

with this premium video cable

Take your components to optimum performance. This top of the line cable offers the best connection for transferring video signals between components.

Enjoy better picture quality
- 24 carat gold-plated connectors optimize signal
- 4-Cut connectors for secure connections
- Split center pin for better signal transfer
- 99.97% Oxygen-Free Copper (OFC)

Protects against signal loss
- 100% aluminum shielding
- Oxygen-free copper conductor for ideal signal transfer
- Copper braided shielding
- Foam Polyethlene (FPE) Dielectric

Easy installation
- Color coded connectors for instant recognition

Enjoy extended durability
- Super pliable jackets for outstanding flexibility
- Reliable metal strain relief

PHILIPS
sense and simplicity

Component video cable
6 ft

SWV6302D/17

Specifications

Packaging Data
- Quantity: 1
- Gross weight: .72 kg
- Tare weight: .2 kg
- Net weight: .52 kg
- Length: 270 mm
- Width: 182 mm
- Height: 59 mm
- EAN/UPC/GTIN: 6 09585 13511 6

Outer Carton
- Quantity: 4
- Gross weight: 3.6 kg
- Tare weight: .44 kg
- Net weight: 3.16 kg
- Length: 311 mm
- Width: 267 mm
- Height: 226 mm
- EAN/UPC/GTIN: 2 06 09585 13511 0

Inner Carton
- EAN/UPC/GTIN: 1 06 09585 13511 3
- Gross weight: 1.58 kg
- Height (cm): 20 cm
- Length (cm): 29.5 cm
- Net weight: 1.44 kg
- Tare weight: .14 kg
- Width (cm): 12.5 cm

Product highlights

24 carat gold-plated connector
24 carat gold-plated connectors ensure the best signal quality for your components.

4-Cut connectors
4-Cut connectors ensure secure connections between your component and your cable.

Split center pin
The split center pin allows for better signal transfer and an improved connection to the component inputs.

99.97% OFC solid conducter
99.97% Oxygen-free copper (OFC) cable core provides optimum signal quality.

100% aluminum shielding
This protective layer of aluminum guards against electromagnetic interference for improved signal quality.

Solid high purity OFC
This oxygen-free copper conductor provides the highest accuracy in signal transfer with minimal resistance.

Copper braided shielding
This protective layer of copper blocks radio frequency interference for improved signal quality.

FPE Dielectric
Foam Polyethlene (FPE) dielectric is a superior insulation material that protects against signal loss.

Color-coded connectors
Color coded connections make it easy to install your cable into the correct inputs and outputs

Super pliable jackets
Super pliable PVC jackets are abrasion-resistant for outstanding flexibility and protection against everyday wear and tear.

Metal strain relief
Full metal connector ensures extended durability by preventing damage during use and installation.

Issue date 2008-03-02
Version: 2.0.7
12 NC: 8670 000 30749
UPC: 6 09585 13511 6

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com